

FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5

PORTABLE TERMINAL	OWNING USER	USAGE FREQUENCY
2a	USER A	10
2b	USER B	8
2c	USER C	0
2d	USER D	2
2e	USER E	0


FIG. 6

INTENSITY OF RECEIVED RADIO WAVES	DISTANCE BETWEEN PORTABLE TERMINAL AND DIGITAL COPYING MACHINE
0.00004 - 0.1 MILLIWATT	10 - 500 METERS
0.1 - 0.4 MILLIWATT	5 - 10 METERS
0.4 - 1.1 MILLIWATTS	3 - 5 METERS
1.1 - 10 MILLIWATTS	0 - 3 METERS

FIG. 7

DISTANCE BETWEEN PORTABLE TERMINAL AND DIGITAL COPYING MACHINE	TEMPERATURE OF FUSING ROLLERS
OVER 500 METERS	HEATER OFF
10 - 500 METERS	50 °C
5 - 10 METERS	100 °C
3 - 5 METERS	130 °C
0 - 3 METERS	145 °C

FIG. 8



20040380-010902

FIG. 9




FIG. 10




FIG. 11




FIG. 12

PORTABLE TERMINAL	OWNING USER	USAGE FREQUENCY
6a	USER A	10

FIG. 13

INTENSITY OF RECEIVED RADIO WAVES	DISTANCE BETWEEN PORTABLE TERMINAL AND COMPUTER
0.00004 - 0.1 MILLIWATT	10 - 500 METERS
0.1 - 0.4 MILLIWATT	5 - 10 METERS
0.4 - 1.1 MILLIWATTS	3 - 5 METERS
1.1 - 10 MILLIWATTS	0 - 3 METERS

FIG. 14

DISTANCE BETWEEN PORTABLE TERMINAL AND COMPUTER	TEMPERATURE OF FUSING ROLLERS
OVER 500 METERS	HEATER OFF
10 - 500 METERS	50 °C
5 - 10 METERS	100 °C
3 - 5 METERS	130 °C
0 - 3 METERS	145 °C

2006070" 08204001

FIG. 15




FIG. 16





FIG. 17

DISTANCE BETWEEN PORTABLE TERMINAL AND COMPUTER	TEMPERATURE OF FUSING ROLLERS IN THE PRINTER 7a	TEMPERATURE OF FUSING ROLLERS IN THE PRINTER 7b
OVER 500 METERS	HEATER OFF	HEATER OFF
10 - 500 METERS	50 °C	HEATER OFF
5 - 10 METERS	100 °C	HEATER OFF
3 - 5 METERS	130 °C	HEATER OFF
0 - 3 METERS	145 °C	50 °C

FIG. 18



20060707 08540001